



# ULTRASONIC MONKEY REPELLENT – Power

## PRINCIPLE OF OPERATION:

Ultrasonic Monkey Repellent - Power is an advanced electronic instrument. The monkey repellent sets you free from monkeys with imperceptible ultrasounds. It diffuses ultrasounds at a wide range that is not audible to humans. The working frequency varies automatically from 20 to 65 KHz through 6 different modes available in the device. Randomly variable frequency avoids immunity phenomenon and repels monkeys. It is safe and easy to use.

You will not hear it; it does not disturb or bother you. The ultrasounds stun the monkeys and they have troubles doing the activity i.e. their activities and biting capacity is reduced. This is the main thing we expect so that the activities of monkeys become ineffective. The device is creating the NON COMFORT ZONE for monkeys so that they stop coming and avoid the place where the device is ON. It may take 4 to 8 weeks to start getting satisfactory results.

## FEATURES

- Automatically, randomly ultrasonic sound generated ranged from 20 kHz to 65 kHz.. So that immunity factor is avoided.
- Different Selections modes are available.
- Smooth and Disaster Mode for faster results
- Adjustable strength of output sound level.
- The effective range is about 3000 to 5000 square feet.

## OPERATION INSTRUCTION & TECHNICAL SPECIFICATION

- Turn on the power,
- To test the device sound turns the switch at section "1". Do not put the unit closed to your ear since the sound volume is great to hurt the ear.
- Initially put in the device in mode 2 for few weeks
- Put the device in disaster mode initially then at Smooth mode.
- Later on then put the repellent at mode 6

## EFFECTIVE COVERAGE AREA:

- About 3000 to 5,000 square feet in open area, 1050 square feet in closed area.

## HIGHLIGHTS

- Smooth & Drastic Mode
- Randomly Variable Frequency
- High Efficiency
- Six Selection Mode - Modulated up to 65 KHz
- Simply Plug In Instrument
- Full Metallic Body
- Safe & Easy to use

**POWER SUPPLY:** 220 V / 50 Hz AC

**DIMENSION & WEIGHT:** 19.5 cm x 16 cm x 10 cm

**WEIGHT:** 1 KG      **MOC:** Metal

## FREQUENCIES:

- 12 – 65kHz ( in 6 sections are as follow).
- Model 1) Ranged from 5kHz to 15kHz. ( Testing Mode )
  - Model 2) Ranged from 15kHz to 30kHz.
  - Model 3) Ranged from 25kHz to 40kHz.
  - Model 4) Ranged from 25kHz to 45kHz.
  - Model 5) Ranged from 35kHz to 45kHz.
  - Model 6) Ranged from 20kHz to 65kHz.

## APPLICATION AREAS

**For Agriculture Land, Factory Gates, Canteens, Restaurants, Warehouses, Farms, Bungalows etc**

## PREVENTIVE MAINTENANCE:

- Protect the device from Water / Rain / High temperature
- Regularly clean the device with cloth so that dust is not accumulated
- The device can be cleaned with air blowers (very low pressure)
- Switch off the device for few hours once in a month
- To test the sound turn the switch at section "1". You will hear a sonic sound. (Do not put the unit closed to your ear since the sound volume is great to hurt the ear) The sound indicates the device is working smoothly. If not contact your service provider